6 CHANNEL NVR

Secuview

Brand: Secuview

Model no: SV-N6506-H1





- 6Ch H.265 4K Network Video Recorder
- Support maximum 8MP IP camera preview & playback
- H.264/H.265 video format coding or decoding
- 80Mbps incoming and outgoing bandwidth
- HDMI output resolution: up to 4K (3840×2160)/60Hz
- All channel synchronous real-time playback
- Plug and play to connect third party ONVIF IP cameras
- Recording resolution up to 8 mega pixel
- All channel synchronous live view and playback by smartphone
- Support 6Ch audio in and support tw-way audio:
- 1x RCA (2.0 Vp-p, 1K Ω) and
- 1 audio output
- 1pc. 8TB Hard disk supported
- 1 self-adaptive 10/100M RJ45 interface
- Instant playback for assigned channel during multi-channel live view mode
- Smart search for selected are in the video, and
- smart playback to improve efficiency
- USB: Rear panel: 1x USB3.0 / 1x USB2.0

Main Processor	Dual-core embedded processor
Operating System	Embedded LINUX
IP Camera Input	6 channel
Two-way talk	1 channel input, 1 channel output, RCA
Interface	1 HDMI, 1 VGA
Display Resolution	1920×1080, 1280×1024, 1280×720, 1024×768
Display Split	1/6
OSD	Camera title, Time, Video loss, Camera lock,
	Motion detection, Recording
Compression	H.264/MJPEG
Recording Resolution	1080P(1920×1080) / 720P(1280×720) /
	D1(704×576/704×480)& etc
Record Rate	Max 56Mbps
Bit Rate	48~8192kbps
Record Mode	Manual, Schedule(Regular(Continuous), MD),
	Stop
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30
	sec, Post-record: 10~300 sec
Trigger Events	Recording, PTZ, Tour, Video Push, Email, FTP,
	Buzzer & Screen tips
Video Detection	Motion Detection, MD Zones: 396(22×18), Video
	Loss & Camera Blank
Sync Playback	1/6
Search Mode	Time/Date, MD & Exact search (accurate to
	second), Smart search

Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play,
	Next file, Previous file, Next camera, Previous
	camera, Full screen, Repeat, Shuffle, Backup
	selection, Digital zoom
Backup Mode	USB Device/Network/Internal SATA burner
Ethernet	1RJ-45 port (10/100Mbps)
PoE	4 ports (IEEE802.3af/at)
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP,
	NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP
	Search(Support Dahua IP camera, DVR, NVS and
	etc.), SNMP, P2P
Smart Phone	iPhone, iPad, Android
Internal HDD	1 SATA port, up to 4TB
USB	2 ports (1 Rear), USB2.0
Power Supply	Single, DC48V/1.25A
Power Consumption	NVR: 10W(without HDD)
	PoE: Max 25.5W (single port)
Working Environment	-10°C~+55°C/10%~90%RH/86~106kpa
Dimension(W×D×H)	Mini 1U, 325mm×250mmx55mm
Weight	1.25kg(without HDD)