## **8 CHANNEL NVR**

**Secuview**®

**Brand**: Secuview

Model no: SV-N6508P-H1



## Main features

- 8Ch H.265 4K Network Video Recorder
- Support maximum 8MP IP camera preview & playback
- H.264/H.265 video format coding or decoding
- 80Mbps incoming and outgoing bandwidth
- HDMI output resolution: up to 4K (3840×2160)/60Hz
- All channel synchronous real-time playback
- Plug and play to connect third party ONVIF IP cameras
- Recording resolution up to 8 mega pixel
- 8Ch POE RJ45 interfaces with maximum power 240W
- All channel synchronous live view and playback by smart phone
- Support 8Ch audio in and support two-way audio:
- 1x RCA (2.0 Vp-p,  $1k\Omega$ ) and 1 audio output
- 1pc 8TB Hard disk supported
- 1 self-adaptive 10/100M RJ45 interface
- Instant playback for assigned channel during multi-channel live view mode
- Smart search for selected area in the video, and
- Smart playback to improve the efficiency
- USB: Rear panel: 1x USB3.0 / 1x USB2.0

	T
Main Processor	Dual-core embedded processor
Operating System	Embedded LINUX
IP Camera Input	8 channel
Two-way talk	1 channel input, 1 channel output, RCA
Interface	1 HDMI, 1 VGA
Display Resolution	1920×1080, 1280×1024, 1280×720, 1024×768
Display Split	1/8
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Compression	H.264/MJPEG
Recording Resolution	5Mp(2560×1920)/3Mp(2048×1536)/1080P(1920×1080)/720P(1280×720)/D1
	(704×576/704×480)
Record Rate	80Mbps
Bit Rate	48~ 8192kbps
Record Mode	Manual, Schedule(Regular(Continuous), MD), Stop
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer & Screen tips
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank
Sync Playback	1/8
Search Mode	Time/Date, MD & Exact search (accurate to second), Smart search
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next
	camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection,
	Digital zoom
Backup Mode	USB Device/Network/Internal SATA burner
Ethernet	1RJ-45 port (10/100Mbps)
PoE	8 ports (IEEE802.3af/at)

Network Function	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter,
	PPPOE, DDNS, FTP, IP Search(Support Dahua IP camera, DVR, NVS and etc.),
	SNMP, P2P
Smart Phone	iPhone, iPad, Android
Internal HDD	1 SATA port, up to 4TB
USB	2 ports (1 Rear), USB2.0
Power Supply	Single, DC48V/1.25A
Power Consumption	NVR: 10W(without HDD)
	PoE: Max 25.5W (single port)
Working Environment	-10°C~+55°C/10%~90%RH/86~106kpa
Dimension(W×D×H)	Mini 1U, 325mm×250mmx55mm
Weight	1.25kg(without HDD)