

Model Number:

SV-G412B01



Specification

Product Size	216*133mm
CPU	MT7628 580MHz
Memories	FLASH 8M, DDR 64M
Protocols Comply	IEEE802.11b/g/n/ac, IEEE802.3u, IEEE 802.3x
Wi-Fi	2.4GHz: 300Mbps, 2.412 GHz ~ 2.484GHz (Channel 1~13) 5.8GHz: 866Mbps, 5.180 GHz ~ 5.850 GHz (Channel 36~165)
Ethernet Ports	2x 10/100M LAN 1x 10/100M WAN
4G Modem	LTE CAT4 MIMO 2*2, Maximum downlink150Mbps and uplink 50Mbps
Power Supply	DC 12V/1A
SIM Slot	1, Standard 25*15mm
Reset Button	1x Reset button, Restore factory default settings
Antenna	Wi-Fi 5dBi x 4PCS, 4G 5dBi x 2PCS
LED Indicator	PWR, WAN, LAN1, LAN2, WiFi, 4G
Working Temperature	-25°C~+60°C
Storage Temperature	-40°C~+80°C
Working Humidity	10%~95% RH (non-condensation)
Storage Humidity	10%~95% RH (non-condensation)

Website

www.starfoxsecu.com / www.secuview.com