

**Model Number:**  
SV-AP612SX03



## Specification

Product Size	190*190mm
CPU	MT7628
Memories	FLASH 16M, DDR 256M
Protocols Comply	IEEE802.11b/g/n, IEEE802.3u, IEEE 802.3x
Wi-Fi	2.4GHz: 300Mbps, 2.412 GHz ~ 2.472 GHz (Channels 1~13) 5GHz : 866Mbps, 5.180 GHz ~ 5.850 GHz (Channel 36~165)
TX Power	2.4GHz: 100mW, 5GHz: 100mW
Ethernet Ports	2x 10/100M LAN/WAN
Power Supply	DC 12V 1A, Passive POE 48V
Modulation Type	OFDM/BPSK/QPSK/DQPSK/DBPSK
Reset Button	1x Reset button, Restore factory default settings
Antenna	2.4G built-in 5dBi x 2PCS, 5.8G built-in 5dBi x 2PCS
LED Indicator	PWR,WAN
Working Temperature	0°C~+55°C
Storage Temperature	-30°C~+80°C
Working Humidity	10%~95% RH (non-condensation)
Storage Humidity	10%~95% RH (non-condensation)

Website

[www.starfoxsecu.com](http://www.starfoxsecu.com) / [www.secuview.com](http://www.secuview.com)