

Model Number:

SV-P81202NA



Specification

Item		Description
Power	Input voltage	AC100-240V
	Output voltage	DC48V~52V
	Total Power	120W, Built-in power supply
Network Connector	Network Port	1~8 Port : 10/100Mbps POE Ethernet Port
		9~10 Port : 10/100Mbps Uplink Port
	Transmission Distance	1~8 Port: 0~100m or 250m(Switch to select distance)
		9~10 Port : 0~100m
Transmission Medium	Cat5/5e/6 standard network cable	
Network Switch	Network Standard	IEEE802.3X, IEEE 802.3i 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE802.1Q, IEEE802.3az.
	Switching Capacity	2Gbps
	Packet Forwarding Rate	1.488Mpps
Power Over Ethernet	POE Standard	IEEE 802.3af/at
	POE Power Consumption	af≤15.4W , at≤30W , (POE port)
	Connection Pins	Data pins:100M:12 +/36-, power pins: 12+36-
LED Status Indicator	POE Ethernet LED Indicator	Power: 1 red light indicates that the power normal work;
		POE: 8 yellow lights indicate that the POE is power on;
		Ethernet: 10 green lights indicate that the Ethernet link and act;
Environmental	Working temperature	0 ~55
	Relative Humidity	20~95% non-condensing
	Storage temperature	-20 ~70
Mechanical	Dimension (L×W×H)	202*140*45mm
	Color	Black
	Weight	1.1kg
Stability	MTBF	>30000h

Website

www.starfoxsecu.com / www.secuview.com