

**Model Number:**  
SVA4016



## Specification

<b>Power supply voltage:</b>	AC 220V or AC 110V, 50-60Hz
<b>Power dissipation:</b>	≤20VAe
<b>Exchange mechanism:</b>	Analog switch matrix
<b>Caller ID receiving mode:</b>	DTMF & FSK
<b>Caller ID sending mode:</b>	DTMF & FSK@
<b>Type of telephone:</b>	Dual Tone Multi-Frequency
<b>Dial mode:</b>	Tone frequency signal
<b>Communications path:</b>	7
<b>Feed on Ext port:</b>	DC38V 20-30mA
<b>IC Power Supply:</b>	±5V
<b>Distortion:</b>	≤10%
<b>Ringing Voltage:</b>	AC 70V±10% 50HZ
<b>Internal dial tone:</b>	380HZ Continuous square wave
<b>Internal ring back tone:</b>	380HZ square wave 1s on, 4s off
<b>Internal busy tone:</b>	380HZ square wave 0.3s on, 0.3s off
<b>Internal verification tone:</b>	380HZ square wave 0.3s on, 0.3s off
<b>CO line prompt tone:</b>	380HZ square wave 2s on, 5s off
<b>External music interface:</b>	input voltage rang 0.5V~2.0V
<b>CO line tone:</b>	depend on service provider

Website

[www.starfoxsecu.com](http://www.starfoxsecu.com) / [www.secuview.com](http://www.secuview.com)