



# Secuview 300W 16 PoE + 2 Uplink + 2 SFP Ports Gigabit PoE Switch

**Model Number:**  
SV-GP163004GB



## Specification

| ITEMS  |                                  | DESCRIPTION   |
|--|----------------------------------|---|
| Power  | Input voltage                    | AC100-240V  |
|  | Output voltage                   | DC48V~52V   |
|  | Consumption                      | 200W / 300W   |
| Network Connector                              | Network Port                     | 1~16 Port : 10/100/1000Mbps POE Ethernet Port   |
|  |                                  | 17~18 Port : 10/100/1000Mbps Uplink Port  |
|  |                                  | 19~20 Port : 1.25Gbps SFP Port  |
|  | Transmission Distance            | 1~16 Port : 0~100m  |
| 17~18 Port : 0~100m                            |                                  |   |
| 19~20 Port : depends on the SFP optical module |                                  |   |
| Transmission Medium                            | Cat5/5e/6 standard network cable |   |
| Network Switch                                 | Network Standard                 | IEEE802.3X, IEEE 802.3i 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3ab 1000BASE-T, IEEE 802.3z 1000Base-X, IEEE802.1Q, IEEE802.3az. |
|  | Switching Capacity               | 56Gbps  |
|  | Packet Forwarding Rate           | 41.664Mpps  |
| Power Over Ethernet                            | POE Standard                     | IEEE 802.3af/at   |
|  | POE Power Consumption            | af≤15.4W , at≤30W , (POE port)  |
|  | Connection Pins                  | Data pins: 45+78-, power pins: 12+36-   |
| LED Status Indicator                           | POE Ethernet LED Indicator       | Power: 1 red light indicates that the power normal work;  |
|  |                                  | POE: 16 yellow lights indicate that the POE is power on;  |
|  |                                  | Ethernet: 20 green lights indicate that the Ethernet link and act;  |
| Environmental                                  | Working temperature              | 0 ~55   |
|  | Relative Humidity                | 20~95% non-condensing   |
|  | Storage temperature              | -20 ~70   |
| Mechanical                                     | Dimension (L×W×H)                | 305*225*45mm  |
|  | Weight                           | 3100g   |
| Stability                                      | MTBF                             | >30000h   |

Website

[www.starfoxsecu.com](http://www.starfoxsecu.com) / [www.secuview.com](http://www.secuview.com)