

### Model Number:

SV-4K1004-M8



### Key Features

- > Support 4ch 8M unreal-time encoding;
- > Support Xvi, AHD, TVI, CVI, CVBS, IP video input;
- > support VGA maximum 1080P output, HDMI up to 4K output;
- > Mini 1U Case, 1\*SATA(Up to 14TB);
- > 1\*10/100Mbps auto-sensing Ethernet port, RJ45 port;
- > Automatic networking support, a key to add equipment;
- > Support the Onvif protocol;
- > Support GB28181 (Optional);
- > Cloud services, P2P, alarm information push to phone;
- > Support remote access, support ARSP;
- > Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc;
- > Mobile phone remote monitoring (iOS, Android);
- > Multi browser access (IE, Chrome, Firefox, Safari);
- > Support for more than twenty languages;
- > Perfect protection circuit, unique triple watchdog function
- > Support WEB, CMS, VMS, MYEYE Platform;
- > Support coaxial control
- > Support coaxial audio
- > Support human detection, face detection and other intelligence

## Specification

Model	SV-4K1004-M8	
System	Processor	NT98332
Video	Codec	H.265+/H.265/H.264
	Preview	4ch8M@15fps(6 in 1)/4ch5M@20fps(6 in 1)/ 4ch4M(6 in 1) /4ch3M (6 in 1)/4ch1080P(6 in 1) default8M
	Encode	4ch8M@8fps(6 in 1)/4ch5M@16fps(6 in 1)/ 4ch4M@21fps(6 in 1) / 4ch3M@25fps(6 in 1)/4ch1080P(6 in 1) default8M
	Decode	4ch8M@8fps(6 in 1)/4ch5M@16fps(6 in 1)/4ch4M@21fps(6 in 1) /4ch3M@25fps(6 in 1)/4ch1080P(6 in 1) default8M
	Multi-mode	Analog: 4ch 8M
		hybrid: 4*8M (analog) +4*8M (network) IP:16ch 1080P/8ch 5M
	Playback	4/2/1ch
Audio	Compression	G.711a
	Coaxial audio	Support
	Intercom	Support
Management	Record mode	Manual>Alarm>Motion detection>Timing
	Inquire mode	Inquire by Time/Calendar/Event/Channel
	Storage mode	HDD Storage, Network Storage
	Backup	Network, USB, SATA
Interface	Video input	4*BNC(Support Coaxitron)
	HDMI output	1*HDMI (MAX:4K)
	VGA output	1*VGA (MAX:1080P)
	Audio I/O	45658
	Alarm I/O	0/0
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port
	PTZ control	Support for multiple PTZ protocol
	USB port	2*USB2.0 ports
	HDD	1*SATA interface (Up to14TB)
General	Temperature	0 - + 55
	Humidity	10% -90% RH
	Power supply	12V/2A
	Consumption	<10W(Without HDD)
	Weight	Around1KG
	Dimension	255mm(L)* 215mm(W)* 44mm(H)

Website

[www.starfoxsecu.com](http://www.starfoxsecu.com) / [www.secuview.com](http://www.secuview.com)