

Model Number:
G4GR300X



Specification

Interface	RJ45	4*lan 1*wan
	RJ11	optional
	SIM	2FF or 4FF or Dual SIM
	Button	reset/wps/Wi-Fi/battery level
	adapter	Input voltage:12V-1.5A
	Battery	7.4V 2 x 2000mAh
Solution	Routing and WiFi chipset supplier	MTK
BASE	Routing and WiFi chipset model	MT7628N
	Routing and WiFi processor info	IEEE 80 2.11 /b/g/n
	DDR/SPI	64MBytes/16MBytes
RF	4G Main antenna	Internal antenna
	4G Receive diversity antenna	Internal antenna
	Wi-Fi band	2400MHz-2483.5MHz
	MIMO for Wi-Fi	5dbi X 2
	Max. transmitter power for WIFI	802.11b 24dBm±2dBm; 802.11g 16dBm±2dBm; 802.11n 15dBm±2dBm;

Software	Language	Chinese & English
	APN Setting	Supported
	Device Settings	Supported
	WIFI Settings	Supported
	Routing Settings	Supported
	Firewall Settings	Supported
	LED	Supported
Technical standard	WiFi standard	802.11b/g/n (2*2 11n features)
	WiFi security	WPA/WPA2
	OS	Windows XP、Windows Vista、Windows 7 8 10、MAC、Linux
	Browser	IE (7.0 and later)、Firefox (3.0 and later)、Safari (4.0 and later)、Opera (10.0 and later)、Chrome (10.0 and later)
Environment	Operating temperature	0 to 50° C
	Storage temperature	-40 to 70° C
	Humidity	5% to 95%

Website

www.starfoxsecu.com / www.secuview.com