

Model Number:

SV-P4652NA



Specification

	Item	Description
Power	Input voltage	AC100-240V
	Output voltage	DC48V~52V
	Total Power	65W, Built-in power supply
Network Connector	Network Port	1~4 Port : 10/100Mbps POE Ethernet Port 5~6 Port : 10/100Mbps Uplink Port
	Transmission Distance	1~4 Port: 0~100m or 250m(Switch to select distance) 5~6 Port : 0~100m
	Transmission Medium	Cat5/5e/6 standard network cable
Network Switch	Network Standard	IEEE802.3X, IEEE 802.3i 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE802.1Q, IEEE802.3az.
	Switching Capacity	1.2Gbps
	Packet Forwarding Rate	0.89Mpps
Power Over Ethernet	POE Standard	IEEE 802.3af/at
	POE Power Consumption	af≤15.4W , at≤30W , (POE port)
	Connection Pins	Data pins:100M:12 +/36-, power pins: 12+36-
LED Status Indicator	POE Ethernet LED Indicator	Power: 1 red light indicates that the power normal work;
		POE: 4 yellow lights indicate that the POE is power on;
		Ethernet: 6 green lights indicate that the Ethernet link and act;
Environmental	Working temperature	0 ~55
	Relative Humidity	20~95% non-condensing
	Storage temperature	-20 ~70
Mechanical	Dimension (L×W×H)	130*120*35mm
	Color	Black
	Weight	0.55kg
Stability	MTBF	>30000h

Website

www.starfoxsecu.com / www.secuview.com