

Model Number:

SVC-M6X4IPTZB

Key Features

- > 1/2.7" CMOS sensor
- > FHD resolution 3840 x 2160P
- > Low illumination 0.01Lux
- > Day/Night (ICR), AWB, 2D/3D-DNR, IR-CUT
- > D-WDR, Motion Detection, Privacy Mask, Mirror, rotate
- > RTSP and Onvif 2.6 compatible
- > H.265/H.264 dual-stream media server
- > Easy-to-use P2P Cloud service
- > Multi web browser, PC Client, mobile APP remote access
- > Optional customization Lens/Audio/POE, etc.
- > Lightning protection 4000V
- > Strong water-proof housing, IP66
- > 6 pcs SMD Array IR Leds, IR distance 20-30 meters
- > Network PTZ control , 5 times optical zoom
- > HD 2.7-13.5 mm Auto Focus Motorized lens
- > Support two-way Audio



Specification

Model	SVC-M6X4IPTZB
Camera	
Image Sensor	1/2.7" CMOS senso
Effective Pixels	3840*2160P
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto/Manual
AGC/BLC	Support
DNR	2D/3D DNR
Other	Multi-lines OSD, Motion Detection, Privacy Mask, Mirror, Rotate
Encode	
Video Standard	H.265/H.264

Video Resolution	MainStream:15fps@8MP(3840x2160), 30fps@6MP(3072x2048)/5MP(2592x1944)/4MP/3MP/1080P/720P, etc.
	Sub stream: 720x480/VGA(640x480)/360P/QVGA@30fps, etc.
Video Bitrates	64Kbps - 8Mbps, VBR/CBR
Audio Standard	G.711-u/G.711-a
OSD Overlay	Title and Time overlay
IR Led	
IR Led	6 pcs SMD array IR Led
IR Distance	20-30M
Lens	
Focal length	2.7-13.5 mm AF lens
Zoom	5x optical zoom
Optional Function	
POE, Audio, etc.	
PTZ	
Pan/Tilt Range	Pan: 0° ~ 180°; Tilt: 0° ~ 55°
Preset Point	1
Manual Control Speed	Pan: 0.5° ~20° /s; Tilt: 0.5° ~10° /s
Guard Position	Support
Network Services	
Protocol	HTTP/RTSP/FTP/NFS/SMTP/DHCP/NTP, etc.
Web	IE , Firefox, etc.
Media	CMS, Android, IOS
ONVIF	17.06 compatible
General	
Network Port	1-RJ45, 100Mbps, POE optional
Power Supply	12 VDC ± 10%
Power Consumption	< 10 W
Operating Temp.	-20°C-(+60)°C, 10%-90%RH

Dimensions:

