

Model Number:
SV-APGR618OX04



Specification

HARDWARE SPECIFICATIONS

CPU	MT7621
FLASH	16MB
DDR	256MB
Wired standard	IEEE802.3,IEEE802.3u,IEEE802.3ab
Ethernet interface	10/100/1000Mbps WAN port*1 support PoE 48V; 10/100/1000Mbps LAN port*1
Antenna	2.4GHz : 3dbiBuilt in omnidirectional antenna ; 5.8GHz : Built in directional antenna
Push-button	Reset Button *1
Power	PoE 48V
Pilot lamp	LED*2(LAN、 WAN)

SOFTWARE SPECIFICATIONS

MESHG networking	support
Micro AC function	Support (When there is no AC in the network, the AP can be set to Micro AC, and logging in to any of them can view and manage all APs in the network)
Number of SSIDs	4 (2.4GHz) +4 (5GHz)
Wireless encryption	Supports encryption/non encryption/hiding
User isolation	Terminal isolation
Wireless MAC address filtering	Support for black and white lists
VLAN settings	support

Transmission power setting	support
Bandwidth settings	support
Channel Settings	support(Supports automatic optimization of optimal channels)
Wireless client limit	support
Device Management	Support Chinese, English, Spanish WEB management
System log	support
Restore factory settings	support
Backup Configuration	support
Import Configuration	support
Software upgrade	support
Network Diagnostics	support
WIRELESS SPECIFICATIONS	
Wireless standards	IEEE 802.11a/b/g/n/ac/ax
Wireless rate	2.4GHz:574Mbps, 5.8GHz:1200Mbps
Wireless encryption method	WPA-PSK,WPA2-PSK,WPA-PSK/WPA2-PSK
OTHER	
Working Temperature	-40 ~80
Storage Temperature	10%~90% RH (non-condensation)
Working Humidity	-40 ~80
Storage Humidity	5%~90% RH (non-condensation)
Product Size	86*86*46mm

Website

www.starfoxsecu.com / www.secuview.com